

DALI HIGHBAY ADAPTER | Sensors



Product family features

- DALI adapter for HIGH BAY and VISION sensor
- Light regulation for mounting heights of up to 13 m
- Power supply for coupler from DALI
- Integrated light sensor

Product family benefits

- Test procedures for rapid error-free installation without software

Areas of application

- Industry
- Production halls
- Logistic centers


Product datasheet

Technical data

Electrical data

Nominal voltage	20.0 V
Mains frequency	0 Hz

Dimensions & weight



Height	37.0 mm
Product weight	74.00 g

Temperatures & operating conditions

Ambient temperature range	0...+50 °C
---------------------------	------------

Capabilities

Dimmable	No
Dimming interface	DALI
Maximum installation height	13 m
Operating range, light sensor	20...800 lx ¹⁾
Type of installation	On-top ceiling mounting

¹⁾ Approximately, measured at the sensor

Certificates & standards

Type of protection	IP20
--------------------	------

Logistical data




Commodity code	853710989900
----------------	--------------

Product datasheet

Equipment / Accessories

- Blind cover included
- Suitable for the DALI Professional light control system

Download Data

File	
	Declarations of conformity 334811_Declaration of conformity – DALI PRO CONT-4 – DALI PRO PB Coupler – DALI PRO Sen
	Installation guide 344177_Operating and Mounting Instructions_DALI HIGHBAY Adapter
	CAD data 3-dim DALI Highbay Adapter CAD Data

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321774132		Shipping carton box 20	270 mm x 225 mm x 285 mm	17.31 dm ³	2668.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.