

EN -SCPPH-1500-ZB

EN-SCPPH-1500-ZB | Sensors



Product family features

- Presence detection via passive IR element
- Light sensor operating range: 0...1,000 lx
- Daylight-dependent regulation and presence-dependent control of light
- Integrated ZigBee Home Automation connectivity
- Battery-powered

Product family benefits

- Multiple sensors can be networked
- Simple installation


Areas of application

- Ceiling surface mounting
- Wide range of applications
- Indoor parking areas

Product datasheet

Technical data

Dimensions & weight



Diameter	86.0 mm
Height	29.0 mm
Product weight	110.00 g

Temperatures & operating conditions

Ambient temperature range	0...+40 °C
---------------------------	------------

Capabilities

Dimming interface	ZigBee HA
Maximum installation height	3 m
Detection area	40 m
Detection angle	136 °
Type of installation	On-top ceiling mounting
Operating range, light sensor	0...1000 lx
Transmitter range	10 m

Certificates & standards

Type of protection	IP20
--------------------	------

Logistical data

Commodity code	852692009000
----------------	--------------

Download Data

File

Product datasheet



Declarations of conformity
EU Declaration of Conformity Encelium Wireless Devices

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899989337	EN -SCPPH-1500-ZB	Shipping carton box 10	264 mm x 167 mm x 225 mm	9.92 dm ³	2259.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.